



Truefashion Projector GCGM

ST700T LED40 930PC PSU WB 1C WH

Truefashion Projector GCGM, 43.8 W, 930 warm white, 34°,
Finger-protected

Truefashion Projector is offering a retail segment with attractive outlook design, excellent quality of light & dedicated light recipe as well as system connectivity, to create a comfortable ambiance and impressive shopping experience to stimulate the store sales for retail customers.

Warnings and Safety

- 3 years

Product data

General Information		Color rendering index (CRI)	
Light source replaceable	No		>90
Number of gear units	1 unit	Beam angle of light source	120 degree(s)
Driver included	Yes	Light source color	930 warm white
Light source engine type	-	Optic type	Beam angle 34°
CE mark	CE mark	Optical cover type	Lens
Warranty period	3 years	Luminaire light beam spread	34°
ENEC mark	-		
EU RoHS compliant	Yes		
Light Technical		Operating and Electrical	
Luminous Flux	3,125.52 lumen	Input Voltage	220 to 240 V
Correlated Color Temperature (Nom)	3000 K	Line Frequency	50 or 60 Hz
Luminous Efficacy (rated) (Nom)	71.4 lm/W	Power Consumption	43.8 W
		Power Factor (Fraction)	0.9
		Connection	Track
		Cable	-

Truefashion Projector GCGM

Number of products on MCB of 16 A type B	-
Temperature	
Ambient temperature range	-20 to +35 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover material	Polymethyl methacrylate
Fixation material	Aluminum
Housing Color	White
Optical cover finish	Clear
Overall length	223 mm
Overall height	185 mm
Overall diameter	80 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	-
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.422, 0.386) SDCM<3
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Driver failure rate at 5000 h	0.23 %
Median useful life L70B50	50,000 hour(s)
Median useful life L80B50	38,700 hour(s)
Median useful life L90B50	18,200 hour(s)
Application Conditions	
Maximum dim level	Not applicable
Suitable for random switching	No
Product Data	
Full product code	911401547761
Order product name	ST700T LED40 930PC PSU WB 1C WH
Order code	911401547761
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401547761
Full product name	ST700T LED40 930PC PSU WB 1C WH

Dimensional drawing

Truefashion Projector GCGM

