



Essential Smartbright T5 Batten

BN058C LED3/WW L300 GM

Essential Smartbright T5 Batten, 3.4 W, 300 lumen, 3000 K

BN058 Batten provide flexibility to customer to choose from 3 CCT and 4 different size and lumen packages, based on their specific need.

Product data

General Information		Temperature	
Light source engine type	LED	Ambient temperature range	-20 to +40 °C
CE mark	-	Controls and Dimming	
Light Technical		Dimmable	No
Luminous Flux	300 lumen	Control interface	-
Correlated Color Temperature (Nom)	3000 K	Mechanical and Housing	
Luminous Efficacy (rated) (Nom)	85 lm/W	Housing Material	Polycarbonate
Color rendering index (CRI)	>70	Optical cover material	Polycarbonate
Light source color	730 warm white	Housing Color	White
Optical cover type	Polycarbonate	Optical cover finish	Opal
Operating and Electrical		Overall length	325 mm
Input Voltage	220 to 240 V	Overall width	21 mm
Line Frequency	50 or 60 Hz	Overall height	32.3 mm
Power Consumption	3.4 W	Dimensions (Height x Width x Depth)	32 x 21 x 325 mm
Power Factor (Fraction)	0.45	Approval and Application	
Number of products on MCB of 16 A type B	8	Ingress protection code	IP20 [Finger-protected]
		Mech. impact protection code	IK02 [0.2 J standard]

Essential Smartbright T5 Batten

Protection class IEC	Safety class II
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Full product code	871016331403799
Order product name	BN058C LED3/WW L300 GM

Order code	911401709612
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	911401709612
Full product name	BN058C LED3/WW L300 GM
EAN/UPC - Case	8710163314273
EAN/UPC - Product/Case	8710163314037

Dimensional drawing

