



Solar Battery Sub System

XGS321 12V/150AH IP68 Gel Bat sys 5yrs

A range of 65 Ah to 250 Ah 12/24V, valve regulated lead acid (VRLA) battery with gel electrolyte technology to get long service lifetime and high performance in deep discharging. It can be used in wide range of ambient temperature and keep good performance of constant power input

Product data

General Information	
CE mark	CE mark
Warranty period	5 years
EU RoHS compliant	Yes
Operating and Electrical	
Input Voltage	12 DC V
Battery type	Gel
Battery ampere hour	150 Ah
Battery voltage	12 V
Battery charging & discharging cycles	750
Cable connection kit	Included
Cable	Cable 2.8 m 4.0 sqmm with KB1 connectors
Temperature	
Ambient temperature range	-20 to +55 °C
Mechanical and Housing	
Overall length	480 mm
Overall width	170 mm

Overall height	300 mm
Dimensions (Height x Width x Depth)	300 x 170 x 480 mm
Approval and Application	
Ingress protection code	IP68 [Dust penetration-protected, pressure watertight]
Application Conditions	
Ambient temperature range for charging	-20 °C to +55 °C
Ambient temperature range for discharging (when light is on)	-20 °C to +55 °C
Product Data	
Full product code	872016972906300
Order product name	XGS321 12V/150AH IP68 Gel Bat sys 5yrs
Order code	911401817302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401817302
Full product name	XGS321 12V/150AH IP68 Gel Bat sys 5yrs
EAN/UPC - Case	8720169729063


Solar Battery Sub System

EAN/UPC - Product/Case

8720169729063


Dimensional drawing

12V Gel Battery Subsystem



Description	Battery Size (cm) LxWxH
MS232 12V/105Ah-IP68 gel battery subsys	35x16,5x21,5
MS232 12V/105Ah-IP68 gel battery subsys	35,5x17,2x21,5
MS232 12V/120Ah-IP68 gel battery subsys	35,5x17,2x21,5
MS232 12V/120Ah-IP68 gel battery subsys	40,5x17,4x21,5
MS232 12V/150Ah-IP68 gel battery subsys	40,5x17,2x21
MS232 12V/150Ah-IP68 gel battery subsys	52,2x23,8x21,8
MS232 12V/150Ah-IP68 gel battery subsys	52,2x23,8x21,8
MS232 12V/220Ah-IP68 gel battery subsys	52,2x26,2x22

24V Gel Battery Subsystem



Description	Battery Size (cm) LxWxH
MS232 24V/105Ah-IP68 Gel Bat. Sys. 2x24	35x16,5x21,5
MS232 24V/105Ah-IP68 Gel Bat. Sys. 2x24	35,5x17,2x21,5
MS232 24V/120Ah-IP68 Gel Bat. Sys. 2x24	35,5x17,2x21,5
MS232 24V/120Ah-IP68 Gel Bat. Sys. 2x24	40,5x17,4x21,5
MS232 24V/150Ah-IP68 Gel Bat. Sys. 2x24	40,5x17,2x21
MS232 24V/150Ah-IP68 Gel Bat. Sys. 2x24	52,2x23,8x21,8
MS232 24V/150Ah-IP68 Gel Bat. Sys. 2x24	52,2x23,8x21,8
MS232 24V/220Ah-IP68 Gel Bat. Sys. 2x24	52,2x26,2x22

