

SJ2000 ALUMINUM SERVICE JACK 2T

鋁合金四輪千斤頂2T

- The main housing made by aluminum material.
- Min. Saddle height: 3-1/2" (87mm).
- Max. Saddle height: 17-1/2" (446mm).
- Hydraulic lift: 14-1/8" (359mm).
- Weight: 34 Lbs (15kgs).

四輪千斤頂 SERVICE JACKS

- Ideally suited for all automotive, agriculture and light truck repair facilities.
- Pump is operated by both activating foot pedal to provide speed to contact the load, and activating "T" handle to lift it.
- Hydraulic power unit with dust seals to prevent oil contamination.
- Large heavy duty rear swivel caster wheels provide easy maneuvering and positioning of jack.

編號 Item	能力 Capacity	行程 Height range	體積 Size(LxWxH)	包裝 Packing(N.W./G.W./CUFT)
SJ2500	2.5T	145~520mm	695x344x180	36.5/38.5/1.96'
SJ3000	3T	120~580mm	1322x326x1037	69/71/4.9'
SJ5000	5T	120~580mm	1322x365x1037	80/82/5.3'

氣囊式千斤頂 AIR BAG SERVICE JACKS

- Air pressure, speedy and safe. The main power via air pressure for quick action.
- With safe valve.

編號 Item	CAP. (Tons)	Type balls	Mini (mm)	Max (mm)	Air pressure kg/cm ²
SJ22	2	2	130	320	5-7
SJ23	2	3	150	400	5-7



US1175 UNDER HOIST STAND

圓柱型支撐架(標準型)

- Capacity: 3/4 ton
- Height range: 1400-2065mm
- Base size: ϕ 305mm

US1180 UNDER HOIST STAND

圓柱型支撐架(腳踏型)

- Capacity: 3/4 ton
- Height range: 1400-2065mm
- Base size: ϕ 305mm
- Controlled by foot

