

# Product datasheet

Specifications



## Vivace 16A SCHUKO-SOCKET OUTLET WITH SHUTTER

KB426\_16S\_WE\_G3

### Main

Range	Vivace
Product or component type	Socket-outlet
Device short name	KB426
Device application	Power supply
Device presentation	Complete mechanism
Outlet standard	Schuko
Colour tint	White

### Complementary

Outlet poles configuration	2 x 2P + E with shutters
Number of gangs	1 gang
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	16 A at 250 V AC, resistive 16 A at 250 V AC, inductive
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	E L N
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm <sup>2</sup>
Width	86 mm
Height	86 mm

## Environment

Standards	IEC 60884
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.9 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	104 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.11 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	21 cm
Package 3 Width	31.5 cm
Package 3 Length	50 cm
Package 3 Weight	10650 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Recommended replacement(s)