



1034 AIR OPERATED GREASE PUMP

氣動黃油機

- Uses air as power to suck grease into lubrication points.
- Suitable for 00#-2# grease.
- Capacity: 20L.
- Air inlet pressure: 4-9kgs/cm.
- Pressure ratio: 45:1.
- Grease output pressure: 180-405kgs/cm
- Deliver rate: 30cc/sec.



• 1034p Pressure plate (optional)



4254 200L PNEUMATIC OPERATED GREASE PUMP

200L 氣動式黃油機

Features:

- Suits grease 00#-2# of original 50 gallons pack of worldwide brands
- There are two independent & separate cycle systems of pump out there, which prevents air-compressor-exhaust moisture from getting to the grease inside the barrel and deteriorating its quality.
- Applicable: All sorts of machinery, vehicles, airplanes, ships, etc.
- Capacity: 200L; Hose length: 20ft.
- Air input pressure: 4-9 bar(60-130psi); Grease output pressure: 180-405bar(2700-5850psi).
- Pressure ratio: 45:1; Deliver ratio: 30c.c./second.



4331 PRESSURE BRAKE BLEEDER

氣壓式剎車油交換機

- Air operated pressure brake bleeder.
- Suitable for clutch bleeder as well as brake bleeder.
- Complete master cylinder adapter kit included.
- Capacity: 5L.
- AIR Inlet: 1/4" PT.



4332 ELECTRIC BRAKE BLEEDER

電動式剎車油交換機

- Electric operated pressure brake bleeder.
- Suitable for clutch bleeder as well as brake bleeder.
- Special designed adapters for European ABS car series.
- Regulate voltage, automatically turn-off to protect brake system.
- Capacity: 5L.
- Power: DC12V.

