

**4324 WRINKLE BAND PISTON RING COMPRESSOR****固定鉗式活塞環夾**

Contents:

- Simply set the adjustment screw once for the complete job.
- Reduce ring friction, slides into cylinder easily.
- Unique wrinkle band will not slip down into cylinder.
- Capacity: 3" to 5" (75 to 125mm).
- Depth: 1-1/2" (38mm).

**1734 PISTON RING COMPRESSOR****活塞環夾3" x 125mm**

- Self locking ratchet pawl prevents premature release and allows positive locking action.
- 3" height, capacity 2-1/8" to 5" (53-125mm)

**1735 PISTON RING COMPRESSOR****活塞環夾3" x 175mm**

- Self locking ratchet pawl prevents premature release and allows positive locking action.
- 3" height, capacity 3-1/2" to 7" (90-175mm)

**1736 PISTON RING COMPRESSOR****活塞環夾4" x 175mm**

- Self locking ratchet pawl prevents premature release and allows positive locking action.
- 4" height, capacity 3-1/2" to 7" (90-175mm)

**1737 PISTON RING COMPRESSOR****活塞環夾6" x 175mm**

- Self locking ratchet pawl prevents premature release and allows positive locking action.
- 6" height, capacity 3-1/2" to 7" (90-175mm)

**1348 ADJUSTABLE PISTON RING INSTALLER****活塞環撥開鉗**

- Make installing piston rings safe and easy without over-expanding rings.
- Works on most common piston diameter.
- Capacity: 3/64" to 1/4" thickness.

**4007 HEAVY DUTY PISTON RING INSTALLER****強力型活塞環撥開鉗**

- Save by reducing ring breakage.
- Tapered jaws to remove and install most passenger car and light truck rings.
- Capacity: 3-1/4" ~ 5-5/16" (83~135mm).

**德式活塞環撥開鉗 PISTON RING INSTALLER**

- Made from special steel.
- Nickel-plated.
- For removing and mounting piston rings.

編號 Item	能力 Range
4008	50~100mm
4009	80~120mm
4010	110~160mm