

## 4055 WISHBONE EXTRACTION TOOL

### 強力型槓桿拉拔器

- Designed sliding groove for adjusting the position to work easily.
- To push down the wishbone and other suspension parts, e.g. during the disassembly of the drive shaft, during replacing the gaiter or exchange of the wheel bearing. After loosening the ball joint, in most cases the wishbone must be pushed down against the bush or stabilizer tension in order to pull the joint from the support.
- With this lever tool, the work can comfortably and surely be accomplished by one person.



## 4650 OPEL REAR SUSPENSION BUSH REMOVAL TOOL

### OPEL 鐵套拆卸器

- For removing and replacing rear upper and lower bushes on trailing arm suspensions.
- Applicable: Opel Vauxhall, Vectra model.



## 4651 FORD REAR SUSPENSION BUSH TOOL

### FORD 鐵套拆裝器

- A special design tool for removing and installing the rear subframe.
- Applicable: Ford Mondeo.



## 1559 HONDA REAR TRAILING ARM BUSH

### HONDA 游臂鐵套拆裝組 INSTALLER / REMOVER

- For replacement of the Honda rear trailing arm bush.
- On car maintenance.
- Hook design to mount the tool on trailing arm securely.
- No damage to ABS sensor cable, trailing arm, and parts close to bush during the maintenance.
- Applicable: Honda CR-V 1996/9~2002/8.K6.K8



## 4164 TOYOTA SUB-FRAME BUSH INSTALLER &

### TOYOTA 工字樑鐵套拆裝器 REMOVER

- Removal and installation of rear rubber mounts of axle suspension.
- On car maintenance. Do not need to remove the sub-frame.
- Applicable: TOYOTA.



INSTALL



REMOVE



VIDEO OF INSTRUCTION



## 4091 UNIVERSAL BUSH REMOVE AND INSTALL

### 螺桿式鐵套拆裝器(通用型) SLEEVE SET

- Universal application of step discs for bearing bush, silent bearing, hydraulic bearing, and rubber bearing on many kinds of different vehicles.
- 20pcs sleeves: ID  $\phi$  34~ $\phi$  72mm (in 2mm increment)
- 2pcs step discs: use with sleeves.
- 4pcs bolts: M10, M12, M14, M16; Length: 450mm.

