



Essential Smartbright T5 Batten

BN058C LED11/CW L1200 GM

Essential Smartbright T5 Batten, 13 W, 1200 lumen, 6500 K

BN058 Batten provide flexibility to customer to choose from 3 CCT and 4 different size and lumen packages, based on their specific need.

Product data

General Information		Temperature	
Light source engine type	LED	Ambient temperature range	-20 to +40 °C
CE mark	-		
Light Technical		Controls and Dimming	
Luminous Flux	1,200 lumen	Dimmable	No
Correlated Color Temperature (Nom)	6500 K	Control interface	-
Luminous Efficacy (rated) (Nom)	85 lm/W		
Color rendering index (CRI)	>70	Mechanical and Housing	
Light source color	765 cool daylight	Housing Material	Polycarbonate
Optical cover type	Polycarbonate	Optical cover material	Polycarbonate
		Housing Color	White
		Optical cover finish	Opal
Operating and Electrical		Overall length	1,185 mm
Input Voltage	220 to 240 V	Overall width	21 mm
Line Frequency	50 or 60 Hz	Overall height	32.3 mm
Power Consumption	13 W	Dimensions (Height x Width x Depth)	32 x 21 x 1185 mm
Power Factor (Fraction)	0.5		
Number of products on MCB of 16 A type B	8	Approval and Application	
		Ingress protection code	IP20 [Finger-protected]
		Mech. impact protection code	IK02 [0.2 J standard]

Essential Smartbright T5 Batten

Protection class IEC	Safety class II
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Full product code	871016331396299
Order product name	BN058C LED11/CW L1200 GM

Order code	911401709542
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	911401709542
Full product name	BN058C LED11/CW L1200 GM
EAN/UPC - Case	8710163314204
EAN/UPC - Product/Case	8710163313962

Dimensional drawing

