

1733 TIRE CONSUMPTION GAUGE**輪胎深度規**

- Determine the average tire residual energy between both positions which is unconsumed part and also is a right barometer for safe driving.
- To brake below tire thread 1.6mm / will bring inferior effect.
- Offers measurement of tire thread from 1-30mm.
- For automobile, below 1.6mm thread depth is recommended for change.
- For truck, below 2.4mm thread depth is recommended for change.

**5150 TIRE GAUGE (ROUND)****圓表型輪胎深度規**

- Gauge dia.: $\phi 47$ mm.
- Testing capacity: 0~1.6mm ● red.
- 1.6~2.0mm ● yellow.
- 2.0~11mm ● green.

**5328 DIGITAL TIRE CONSUMPTION GAUGE****數字型輪胎深度規**

- Large LCD display.
- Range: 0-25.4mm.
- Resolution: 0.01mm.
- Working temperature: 0-40°C.

**3926 SNAP IN TIRE VALVE INSTALLER****氣門風嘴拉拔器**

- Steel constructed tool deep threaded head for positive sealing of all snap-in type passenger car tire valve stems.
- Rubber cover design to protect the rim.
- 3 position settled.
- Patented.

**5630 RIM PROTECTOR****2PCS 輪胎拆卸保護墊**

- To protect the wheel rims from damage.
- Total 2 pos.

**5631 4PCS TIRE LEVER SET****4PCS 輪胎撬棒組**

- Made from forged medium carbon steel.
- Size: 12", 16", 20", 24"

**4219 WHEEL STUD ALIGNMENT GUIDE TOOL****8PCS 小車輪胎定位桿組**

- Assists when mounting wheels, especially late models with long lug bolts.
- Applicable: all Mercedes models with lug bolts.
- Size: 2-M12 x 1.25, 2-M12 x 1.5, 2-M12 x 1.75, 2-M14 x 1.5.

