



GreenUp Round Highbay

BY518P LED260/CW PSU WB GM

GreenUp Round Highbay, 187 W, 26000 lumen, 6500 K

The GreenUp Round Highbay range of luminaires provides the optimal balance between basic performance and price. The family covers a wide product range with a variety of options, competitive specifications, and long-term quality and reliability. The range is suitable for most industrial applications.

Product data

General Information	
Light source engine type	LED
CE mark	CE mark

Light Technical	
Luminous Flux	26,000 lumen
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	139 lm/W
Color rendering index (CRI)	>80
Light source color	865 cool daylight
Optical cover type	Lens

Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Inrush current	0.82 A
Power Consumption	187 W
Power Factor (Fraction)	0.95

Number of products on MCB of 16 A type B 6	
--	--

Temperature	
Ambient temperature range	-20 to +45 °C

Controls and Dimming	
Dimmable	No
Control interface	-

Mechanical and Housing	
Housing Material	Aluminum
Optical cover material	Polycarbonate
Housing Color	Gray
Optical cover finish	Matte
Overall height	99 mm
Overall diameter	358 mm
Effective projected area	0.06 m ²

GreenUp Round Highbay

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.316, 0.332) SDCM<5
Power consumption tolerance	+/-10%

Product Data

Full product code	871951453659399
-------------------	-----------------

Order product name	BY518P LED260/CW PSU WB GM
EAN/UPC - Product	8719514536593
Order code	911401647907
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	911401647907
Full product name	BY518P LED260/CW PSU WB GM
EAN/UPC - Case	8719514536593
EAN/UPC - Product/Case	8719514536593

Dimensional drawing

