



冷媒定量充填站 CHARGING STATION

- Includes the charging cylinder, vacuum pump, charging tester, and special trolley.

編號 Item	規格 Spec
1223	For R-12
1224	For R-134a



1219 CHARGING CYLINDER

冷媒定量充填桶

- Make charging fast and accurate to save your time and money.
- Using a charging cylinder eliminates under-and over-charging which reduces additional servicing.
- It has a precise gauge and a clear calibration that you could charging more quickly and correctly.
- For use on both R-134a, R-12, R-22 systems(3 in 1).
- Capacity: 3200g(7 LB).
- Heater 50W(optional).



1110 VACUUM PUMP

冷媒真空幫浦(推車型)

- Designed for vacuum and pressure test.
- Hose power: 1 hp
- With the relief valve for security, it will stop urgently when it is close to 350psi.
- Has the charging window for survey, and the special designed bottle to separate the oil and water.
- Voltage: AC-110V



真空幫浦 VACUUM PUMP

- For use on R-12 and R134a refrigerants.
- Varies model for your application.

編號 Item	Free Air Displacement	Numbers of Stages	Ultimate Vacuum	Rotating Speed(r/min)	Motor	Power supply
VP130	3CFM	1	150 Microns	1725	1/3HP	115V/60HZ
VP150	5CFM	1	100 Microns	1725	1/2HP	115V/60HZ
VP230	3CFM	2	25 Microns	1725	1/2HP	115V/60HZ
VP250S	5CFM	2	25 Microns	3450	1/3HP	115V/60HZ
VP125	2.5CFM	1	150 Microns	1725	1/3HP	220V/50-60HZ
VP225	2.5CFM	2	25 Microns	1725	1/2HP	220V/50-60HZ
VP245S	4.5CFM	2	25 Microns	3450	1/2HP	220V/50-60HZ