

# UCT-WMTBA (40X17) YE CUS - Cable marker




1014093

<https://www.phoenixcontact.com/pc/products/1014093>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Cable marker, can be ordered: by sheet, yellow, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 6 mm, lettering field size: 40 x 17 mm, Number of individual labels: 3



## Your advantages

- The UCT-WMTBA ... UniCard labeling range includes markers that can be secured using standard cable binders
- Thanks to their angular shape the markers fit perfectly onto cables
- Marking service: Phoenix Contact can custom-mark all UniCard markers according to your requirements
- The format automatically ensures printing with a high degree of positioning accuracy

## Commercial data

Item number	1014093
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8138
Catalog page	Page 271 (NTK-2014)
GTIN	4046356781459
Weight per piece (including packing)	8.58 g
Weight per piece (excluding packing)	8.5 g
Customs tariff number	49119900
Country of origin	PL

# UCT-WMTBA (40X17) YE CUS - Cable marker



1014093

<https://www.phoenixcontact.com/pc/products/1014093>

## Technical data

### Product properties

Product type	Labeled conductor marker
Type	Card form

### Marking

Number of individual labels	3
Number of individual labels per row	1

### Mounting

Mounting type	Assembly with cable ties
---------------	--------------------------

### Material specifications

RoHS compliant	yes
Color	yellow
Material	PC
Flammability rating according to UL 94	V0
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Components	free from silicone, halogen, and cadmium

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

### Dimensions

Width	17 mm
Length	40 mm

#### External dimensions

# UCT-WMTBA (40X17) YE CUS - Cable marker



1014093

<https://www.phoenixcontact.com/pc/products/1014093>

Outside diameter

> 6 mm ... 136 mm

## Standards and regulations

Wipe resistance

DIN EN 61010-1 (VDE 0411-1)

# UCT-WMTBA (40X17) YE CUS - Cable marker



1014093

<https://www.phoenixcontact.com/pc/products/1014093>

## Classifications

### ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

### ETIM

ETIM 8.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)