

Lembar data produk

Spesifikasi



APC Smart-UPS, Line Interactive,
3kVA, Rackmount 2U, 230V, 8x
IEC C13+1x IEC C19 outlets,
Network Card, AVR, LCD

SMT3000RMI2UNC

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead time Usually in Stock

Main

Product or component type Uninterruptible power supply (UPS)

Batteries & Runtime

Run-time [View Runtime Graph](#)

Efisiensi [View Efficiency Graph](#)

Battery type Lead-acid battery

Additional information Configurable for 220 : 230 or 240 nominal output voltage

Extended runtime 0

Number of battery filled slots 0

Number of battery free slots 0

Battery recharge time 3 h

Number of battery replacement quantity 1

Battery life 3...5 year(s)

Replacement battery [RBC43](#)

Battery charger power 182 W rated

General

Provided equipment CD with software
Country-specific detachable power cord
Documentation CD
Installation guide
Rack mounting support rails
Smart UPS signalling RS-232 cable
Temperature probe
USB cable
Web/SNMP management card

Number of power module 0

Number of power module filled slots 0

Number of power module free slots 0

Redundant No

Physical

Number of rack unit	2U
Cable length	2.00 m
Number of cables	1
Colour	Black
Height	8.6 cm
Width	48 cm
Depth	68.3 cm
Net weight	44.19 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

Input

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Input Connection Type	BS1363A British IEC 320 C20 Schuko CEE 7 / EU1-16P
Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2700 W
rated power in VA	3000 VA
output connection type	8 IEC 320 C13 3 IEC Jumpers 1 IEC 320 C19
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Transfer time	4 ms typical
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications	CE EAC IRAM RCM VDE UK PSTI
Marking	GS Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	55 dBA
Heat dissipation	348 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...40 °C
Storage altitude	0...15240 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

control panel	Multifunction LCD status and control console
Emergency power off	Optional
Preinstalled device	Network management card 3 with environmental monitoring
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	320 J
--------------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.500 cm
Package 1 Width	60.000 cm
Package 1 Length	98.500 cm
Package 1 Weight	52.924 kg

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

Environmental Data

Schneider Electric bertujuan untuk mencapai status Net Zero pada tahun 2050 melalui kemitraan rantai pasokan, bahan baku yang lebih rendah, dan beredar melalui kampanye "Use Better, Use Longer, Use Again" untuk memperpanjang masa pakai dan daur ulang produk.

[Environmental Data dijelaskan >](#)

[Bagaimana kami menilai keberlanjutan produk >](#)

Jejak lingkungan

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **2958**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Bahan dan Pengemasan

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant with Exemptions**

SCIP Number **0637234b-27c7-4e32-ae29-543dd4803a99**

REACH Regulation [REACH Declaration](#)

Efisiensi energi

Optimized Energy Efficiency **Energy efficient product**

Use Again

Repak dan remanufaktur

Circularity Profile [End of Life Information](#)

Removable battery **User replaceable**

Take-back **Yes**

Lembar data produk SMT3000RMI2UNC

Image of product / Alternate images

Alternative

