

J. Johnson Wax
Racine, Wisconsin 53403-5011
Phone: (414) 631-2777
Emergency Phone: (800) 228-5635
Extension 092
International Emergency Phone:
(612) 221-3999 Ext 092

4=Very High
3=High
2=Moderate
1=Slight
0=Insignificant

HAZARD RATING		HMIS	NFPA
3	Health		
0	Flammability		
0	Reactivity		

MATERIAL SAFETY DATA SHEET

SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: WAX STRIP				PRODUCT CODE: 630000-3	
CHEMICAL OR COMMON NAME: NA		DATE ISSUED: 04/25/95	SUPERSEDES: NEW	MSDS SECTIONS WITH CHANGES: New	PREPARED BY: Terry A. Meyers Chemical Info. Adm

SECTION II-INGREDIENT INFORMATION

SECTION III-PHYSICAL DATA

APPEARANCE/COOR: Clear liquid with citrus odor	SPECIFIC GRAVITY (H2O=1): 1.1
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): 84- 86
SOLUBILITY IN WATER: Complete	VAPOR DENSITY (Air=1): ND
FREEZING POINT (°F): ND	BOILING POINT (°F): above 200
PH: 12.8Min. (undiluted)	EVAPORATION RATE (Butyl Acetate=1): NA
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (Method Used): NA
FLAMMABLE LIMITS: NA
EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog.
SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Corrosive Material (See Sections VI, VIII).

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Skin contact.
SIGNS AND SYMPTOMS: Direct contact of product with eyes can cause severe irritation and damage. Direct contact of product with skin can cause irritation. If taken internally, product may cause corrosive damage to mouth, throat or stomach.

MATERIAL SAFETY DATA SHEET

Page 2

S.C. Johnson Wax
1525 Howe Street
Racine, Wisconsin 53403

WAX STRIP
Product Number: 630000
Serial Number: 3

SECTION V-HEALTH HAZARD DATA (cont.)

FIRST AID PROCEDURES: Flush eyes with water for 15-20 minutes. If irritation persists, seek medical aid. Wash skin with plenty of water. If irritation persists, seek medical aid. If product is swallowed, drink large amounts of water or milk and seek medical aid. For ingestion, due to the extreme pH of the product, the possibility of corrosive damage to mouth, throat and stomach should be considered in treatment.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders may be more susceptible to irritating effects.

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: Strong acids (e.g., muriatic acid). Aluminum, tin, zinc, and copper alloys

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water.

WASTE DISPOSAL INFORMATION: For undiluted product: Disposal is regulated under the Resource Conservation and Recovery Act as a corrosive waste (40 CFR 261.22). Disposal of regulated quantities should be by neutralization at a permitted facility in accordance with all Federal/State regulations and local ordinances regarding disposal of corrosive wastes. Waste from normal product use may be sewerred to a public-owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: General room ventilation adequate.

PROTECTIVE GLOVES: Rubber.

EYE PROTECTION: For undiluted product: Chemical workers splash-proof goggles

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices. Where gross eye/skin contact may be a problem, wear/use appropriate protective equipment. Wear protective shoes or boots when working with product.

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING: WARNING: Contains caustic alkali. Can cause eye damage. Avoid contact with eyes, skin, and clothing. Harmful if swallowed. Wear eye protection and rubber gloves when handling concentrate. Wear protective shoes or boots when working with product to avoid contact with feet. Keep out of reach of children. FOR INDUSTRIAL USE ONLY.

MATERIAL SAFETY DATA SHEET

Page

S.C. Johnson Wax
1525 Howe Street
Racine, Wisconsin 53403

WAX STRIP
Product Number: 630000
Serial Number: 3

SECTION IX-SPECIAL PRECAUTIONS (cont.)

OTHER HANDLING AND STORAGE CONDITIONS: Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Keep from freezing. Keep out of reach of children. Wash thoroughly after handling.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION:

EPA REGISTRATION #: NA

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: Corrosive Material (Liquid). PG I

DOT #: NA 1760

SHIPPING NAME: Corrosive Liquids (Containing Sodium Hydroxide, Monoethanolamine)

SECTION XII-REGULATORY INFORMATION

All components of this product are listed or are excluded from listing the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined

The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.

2-105 (Rev 5 - 10/90)