

LED Flood Light



Keunggulan:

- Struktur penutup yang kuat
- Material logam berkualitas tinggi
- Cocok digunakan di area outdoor
- Dilengkapi dengan surge protection device (SPD) 1-2KV

Watt yang tersedia:



Material:

Robust die-cast aluminum

Warna yang tersedia:

Kuning Cerah
3.000K

Putih Cerah
6.500K

Jenis Lampu	Warna Cahaya	Lumen
EcoLink FL007 10w/830	Kuning Cerah	750
EcoLink FL007 10w/865	Putih Cerah	800
EcoLink FL007 20w/830	Kuning Cerah	1.500
EcoLink FL007 20w/865	Putih Cerah	1.600
EcoLink FL007 30w/830	Kuning Cerah	2.250
EcoLink FL007 30w/865	Putih Cerah	2.400
EcoLink FL007 50w/830	Kuning Cerah	3.750
EcoLink FL007 50w/865	Putih Cerah	4.000
EcoLink FL007 70w/830	Kuning Cerah	5.250
EcoLink FL007 70w/865	Putih Cerah	5.600
EcoLink FL007 100w/830	Kuning Cerah	7.500
EcoLink FL007 100w/865	Putih Cerah	8.000
EcoLink FL007 150W/865	Putih Cerah	12.000
EcoLink FL007 200w/865	Putih Cerah	16.000



Umur lampu sampai dengan 10.000 jam



Menyala dalam tegangan 220-240V;50/60Hz



Sesuai standar SNI



Adjustable



IKO6 Tahan benturan



IP65 Anti air

EcoLink Floodlight



optical system	Lumen output (typ.Avg)	800, 1600, 2400, 4000, 5600, 8000 lumen
	CRI	≥80
	CCT	3000K and 6500K
	Beam Angle	90° - 110°
Electronics	Input Voltage and Frenquency	220-240V, 50/60Hz
	Lifetime	15,000 H
	Safety Class (driver+system)	Class I
	Driver	Integrated
	Power Factor (system)	>0.9
	Power consumption (system)	10, 20, 30, 50, 70, 100W
	THD	<20%
	System Efficacy	80lm/W
Mechanics	Surge Protection	as IEC Standard
	Housing material	Aluminum Die cast
	Cover	Tempered Glass
	IPxx	IP65
	IKxx	IK06
	Mounting	Adjustable bracket
Approbation	Through wiring	Flying wire
	Approbation	CB, CE, CQC, SNI
Accessories	RoHS/REACH	Yes
	SC, louvres, suspension set, braket,...	Bracket