



# Truefashion Projector GCGM

ST700T LED10 830 PSU WB 1C WH

Truefashion Projector GCGM, 10.7 W, 830 warm white, 30°,  
Finger-protected

Truefashion Projector is offering a retail segment with attractive outlook design, excellent quality of light & dedicated light recipe as well as system connectivity, to create a comfortable ambiance and impressive shopping experience to stimulate the store sales for retail customers.

## Warnings and Safety

- 3 years

## Product data

General Information		Color rendering index (CRI)	
Light source replaceable	No	Color rendering index (CRI)	>80
Number of gear units	1 unit	Beam angle of light source	120 degree(s)
Driver included	Yes	Light source color	830 warm white
Light source engine type	-	Optic type	Beam angle 30°
CE mark	CE mark	Optical cover type	Lens
Warranty period	3 years	Luminaire light beam spread	30°
ENEC mark	-	Operating and Electrical	
EU RoHS compliant	Yes	Input Voltage	220 to 240 V
		Line Frequency	50 or 60 Hz
		Power Consumption	10.7 W
		Power Factor (Fraction)	0.9
		Connection	Track
		Cable	-
Light Technical			
Luminous Flux	1,079.2 lumen		
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	101 lm/W		

# Truefashion Projector GCGM

Number of products on MCB of 16 A type B	-
--	---

## Temperature

Ambient temperature range	-20 to +35 °C
---------------------------	---------------

## Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

## Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover material	Polymethyl methacrylate
Fixation material	Aluminum
Housing Color	White
Optical cover finish	Clear
Overall length	164 mm
Overall height	185 mm
Overall diameter	66 mm

## Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	-
Protection class IEC	Safety class II

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.434, 0.403) SDCM<3
Power consumption tolerance	+/-10%

## Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	0.14 %
Median useful life L70B50	50,000 hour(s)
Median useful life L80B50	50,000 hour(s)
Median useful life L90B50	32,600 hour(s)

## Application Conditions

Maximum dim level	Not applicable
Suitable for random switching	No

## Product Data

Full product code	911401561761
Order product name	ST700T LED10 830 PSU WB 1C WH
Order code	911401561761
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401561761
Full product name	ST700T LED10 830 PSU WB 1C WH

## Dimensional drawing

## Truefashion Projector GCGM

