Lembar data produk

Spesifikasi



Miniature circuit breaker (MCB), Easy9, 1P, 6A, C curve, 4500A (IEC/EN 60898-1)

EZ9F54106

Main

Range	Easy9
Device application	Distribution
Product or component type	Miniature circuit-breaker
Device short name	Easy9 MCB
Poles	1P
Number of protected poles	1
[In] rated current	6 A
Network type	CA
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	4500 A Icn at 230 V AC 50/60 Hz conforming to IEC 60898-1
Suitability for isolation	Yes conforming to IEC 60898-1

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	4500 A 100 % x Icn at 230 V AC 50/60 Hz conforming to IEC 60898-1
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60898-1
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60898-1
Contact position indicator	Yes
control type	Toggle
Local signalling	Without
Mounting mode	Con clip
Mounting support	Carril DIN
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	66.5 mm
Colour	Grey (RAL 7035)
Mechanical durability	10000 cycles

Disklaimer: Dokumentasi ini tidak ditujukan sebagai pengganti dan tidak untuk digunakan untuk menentukan kesesuaian atau keandalan produk ini untuk aplikasi pengguna

Electrical durability	4000 cycles
Connections - terminals	Tunnel type terminal (top or bottom) 1…25 mm² rigid Tunnel type terminal (top or bottom) 1…16 mm² flexible
Tightening torque	2 N.m top or bottom

Environment

Standards	IEC 60898-1
Product certifications	SNI SUCOFINDO
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	2
Overvoltage category	III
Tropicalisation	2
Relative humidity	95 % at -25…60 °C
Ambient air temperature for operation	-5…60 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.48 cm
Package 1 Width	1.77 cm
Package 1 Length	7.27 cm
Package 1 Weight	106.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	2 cm
Package 2 Width	8 cm
Package 2 Length	22 cm
Package 2 Weight	1.272 kg
Unit Type of Package 3	P12
Number of Units in Package 3	2304
Package 3 Height	120 cm
Package 3 Width	80 cm
Package 3 Length	105 cm
Package 3 Weight	258.224 kg

Environmental Data

Schneider Electric bertujuan untuk mencapai status Net Zero pada tahun 2050 melalui kemitraan rantai pasokan, bahan baku yang lebih rendah, dan beredar melalui kampanye "Use Better, Use Longer, Use Again" untuk memperpanjang masa pakai dan daur ulang produk.

Environmental Data dijelaskan >

Bagaimana kami menilai keberlanjutan produk >

Jejak lingkungan

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	**20**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Bahan dan Pengemasan

Recycled metal content at CR level	**0**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant with Exemptions**
SCIP Number	**0dbcf8b1-4732-4e36-88bc-462a078c2d4c**
REACh Regulation	**REACh Declaration**

Use Again

Repak dan remanufaktur

Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**