

扭力型氣門心起子 VALVE CORE TORQUE TOOL

- Prevents over or under torquing.
- Serves as both a core remover and installer.
- Prevents premature tire failure due to leaking valves.
- Easy and simple to use.



編號 Item	設定扭力 Range of the torque	適用風嘴 Valve type	顏色 Color
3523	25N.cm/2 lbf.in(±6%)	RUBBER	Red
3524	45N.cm/4 lbf.in(±6%)	METAL	Black



氣門心起子 VALVE CORE REMOVER / INSTALLER TOOL

- For installation and removal of standard valve cores.
- Has a screwdriver-style handle.

編號 Item	長度 Length	直徑 Diameter
3932	60mm	φ 5.5mm
3932L	160mm	φ 5.5mm



輪胎打氣頭 AIR CHUCKS

編號 Item	全長 Length	頭部內徑 Head I.D.	入風牙規 Input thread	手柄 Handle
5607	150mm	8mm	1/4"PT	Metal
5608	205mm	8mm	1/4"PT	Rubber
5609	350mm	8mm	1/4"PT	Rubber



5611 TIRE PRESSURE GAUGE

棒式輪胎量壓表

- Calibrated in 0.2 kgs/cm²(20kPa) increments from 1 to 11kg/cm²(100~1100kPa) and 2.5 lb/in² from 10 to 160 lb/in².
- Chrome plated and 270mm long.
- Head I.D. is 8mm.

4236 LIGHTWEIGHT 3-FUNCTION TIRE GAUGE-ACCURATE TYPE

輕量型三用打氣量壓表(精準型)

- All the function and weight are the same as JTC-4058.
- Accuracy: between 30~45psi: ± 1psi, the rest: ± 2psi.
- Capacity: 87 psi / 6bar (600KPa).
- Special designed for high accuracy requesting of tire pressure checking.



4058 LIGHTWEIGHT 3-FUNCTION TIRE GAUGE-CLIP TYPE

輕量型三用打氣量壓表(夾式)

- 3 function (check, release, inflator) all together on the press handle.
- Large 80mm gauge with 360° swivel function. Tube length: 600mm.
- Lightweight design for easier operation. Weight: 0.63kgs.
- Accuracy: under 110psi: ± 3psi; above 110psi: ± 4psi.
- Capacity: 170psi/12bar (1200kpa).



4058L LIGHTWEIGHT 3-FUNCTION TIRE GAUGE-PRESS-TYPE

輕量型三用打氣量壓表(壓式)

- All the functions are the same as JTC-4058, but with press type.

