



Technical Data Sheet: PRESTO DN
Wood Glue, Heat Resistance and Solvent Resistance
(JAIA Reg. 003709) Free Formaldehyde F.★★★★
Issued: March 01, 2018



Description:

Presto DN is a specially formulated wood glue with good solvent resistance, heat resistance and initial strength. It has also better sanding properties compares to the conventional PVAC glue.

Applications:

Due to its high solvent resistance, this product is highly suitable where solvent based finishing material is used such as in the production of panel without affecting the glue lines. This Product is also suitable for production of laminated joint board. In addition this adhesive will not soften and smear during sanding hence prolonging the life of sanding belts and cutting tools.

Technical Data

Adhesive Type	: PVAC Emulsion
Color	: Yellow
Viscosity	: 10.000-15.000 cps 5/20/28°C
pH	: 4 ± 1
Solid	: 50 ± 2 %
Specific Gravity	: 1.08
Clean Up	: Water

Packaging:

600 g plastic bottle or
4 kg plastic pail.

Storage and Shelf Life:

Store it at ambient temperature and dry area, avoid exposure to sun and freezing.
The shelf life is 12 months in unopened container.

Manufactured By:

P.T Polychemie Asia Pacific Permai
Jl. Raya Kebayoran Lama no. 15
Jakarta, DKI Jakarta 12220
Indonesia
Office : +62-21 7202563
Mobile : +62-81 83192151
Fax : +62-21 7256911
Website : www.polychemie.co.id
Email : info@polychemie.co.id

The information given and the recommendations made herein are based on our experience and are believed to be accurate.

No guarantee as to or responsibility for their accuracy can be given or accepted, however and no statement herein is to be treated as a representation or warranty. In every case we urge and recommend that purchasers before using any product make their own tests to determine, to their own satisfaction its suitability for their particular purposes under their own operating conditions.